# KODACHROME 25, 64, and 200 Professional Film



#### -NOTICE-

## Discontinuance of KODACHROME 25 Professional Film

KODACHROME Professional 25 Film / PKM has been discontinued.

KODACHROME 64 Professional Film / PKR is the suggested replacement for KODACHROME 25 Professional Film.

#### DESCRIPTION

KODACHROME 25, 64, and 200 Professional Films are color transparency films designed for processing in Process K-14 chemicals. These films are intended for exposure with daylight or electronic flash. You can also expose them with tungsten illumination (3200 K) or photolamps (3400 K) using filters.

KODACHROME 25 and 64 Professional Films feature extremely fine grain and extremely high sharpness. They are excellent choices for a wide variety of professional applications. KODACHROME 200 Professional Film features fine grain and extremely high sharpness. With its faster speed, the film is ideal for low-light situations and photo shoots requiring increased depth of field.

Use these films to produce color transparencies for projection or viewing with 5000 K illumination. Duplicate transparencies can be made by direct printing. To make color prints, you can print transparencies onto color reversal paper. Or make internegatives for printing onto color negative paper. You can also scan transparencies for digital printing and for graphic arts and Photo CD applications.

#### KODACHROME 25 Professional Film / PKM

- Exceptional results in outdoor, travel, nature, advertising, medical, and museum/art applications
- · Extremely sharp
- · Extremely fine grain
- Reproduces subtle color naturally
- Archival (KODACHROME Films are the most archival transparency films)

#### **KODACHROME 64 Professional Film / PKR**

- Excellent for advertising, medical, editorial, and outdoor, travel, and nature applications
- Extremely sharp
- Extremely fine grain
- · Reproduces subtle color naturally
- Archival

#### KODACHROME 200 Professional Film / PKL

- Well suited for sports, editorial, stage-performance, and outdoor/nature applications
- Pushes very well to EI 500 and EI 800 under stadium lighting conditions
- · Natural colors
- 200 speed for stopping action and for use with telephoto lenses
- Extremely high sharpness and fine grain
- Archival

#### SIZES AVAILABLE

#### **KODACHROME 64 Professional Film / PKR**

| Rolls  | Base           | CAT No.  |
|--------|----------------|----------|
| 135-36 | 5.3mil acetate | 187 3041 |

#### STORAGE AND HANDLING

Load and unload film in subdued light.

Store unexposed film in a refrigerator at 55°F (13°C) or lower in the original sealed package. To avoid moisture condensation on film that has been refrigerated, allow the film to warm up to room temperature before opening the package. Process film as soon as possible after exposure.

Protect transparencies form strong light, and store them in a cool, dry place. For more information, see KODAK Publication No. E-30, Storage and *Care of KODAK Photographic Materials—Before and After Processing*.

#### **EXPOSURE**

#### **EXPOSURE INDEX NUMBERS**

Use the exposure index numbers below with cameras or light meters marked for ISO or ASA speeds or exposure indexes. Do not change the film-speed setting when metering through a filter. Metering through filters may affect meter accuracy; see your meter or camera manual for specific information. For critical work, make a series of test exposures.

|                                 | KODAK                     | Exposure Index |     |     |
|---------------------------------|---------------------------|----------------|-----|-----|
| Light Source                    | WRATTEN<br>Gelatin Filter | PKM            | PKR | PKL |
| Daylight or<br>Electronic Flash | None                      | 25             | 64  | 200 |
| Photolamp (3400 K)              | No. 80B                   | 8              | 20  | 64  |
| Tungsten (3200 K)               | No. 80A                   | 6              | 16  | 50  |

#### **Daylight**

Use the exposures in the table below for average frontlit subjects from 2 hours after sunrise to 2 hours before sunset.

| KODACHROME 25 Film / PKM             |                        |                 |
|--------------------------------------|------------------------|-----------------|
| Lighting Conditions                  | Shutter Speed (second) | Lens<br>Opening |
| Bright/Hazy Sun on Sand or Snow      | 1/125                  | f/11            |
| Bright/Hazy Sun, Distinct<br>Shadows | 1/125                  | f/8*            |
| Weak, Hazy Sun, Soft<br>Shadows      | 1/125                  | f/5.6           |
| Cloudy Bright, No Shadows            | 1/125                  | f/4             |
| Heavy Overcast or Open<br>Shade†     | 1/60                   | f/4             |

<sup>\*</sup> Use f/4 for backlit close-up subjects.

<sup>†</sup> Subjects shaded from sun but lit by large area of clear sky.

| KODACHROME 64 Film / PKR             |                        |                 |
|--------------------------------------|------------------------|-----------------|
| Lighting Conditions                  | Shutter Speed (second) | Lens<br>Opening |
| Bright/Hazy Sun on Sand or Snow      | 1/125                  | f/16            |
| Bright/Hazy Sun, Distinct<br>Shadows | 1/125                  | f/11*           |
| Weak, Hazy Sun, Soft<br>Shadows      | 1/125                  | f/8             |
| Cloudy Bright, No Shadows            | 1/125                  | f/5.6           |
| Heavy Overcast or Open<br>Shade†     | 1/125                  | f/4             |

<sup>\*</sup> Use f/5.6 for backlit close-up subjects.

<sup>†</sup> Subjects shaded from sun but lit by large area of clear sky.

| KODACHROME 200 Film / PKL            |                        |                 |
|--------------------------------------|------------------------|-----------------|
| Lighting Conditions                  | Shutter Speed (second) | Lens<br>Opening |
| Bright/Hazy Sun on Sand or Snow      | 1/250                  | f/22            |
| Bright/Hazy Sun, Distinct<br>Shadows | 1/250                  | f/16*           |
| Weak, Hazy Sun, Soft<br>Shadows      | 1/250                  | f/11            |
| Cloudy Bright, No Shadows            | 1/250                  | f/8             |
| Heavy Overcast or Open<br>Shade†     | 1/250                  | f/5.6           |

<sup>\*</sup> Use f/8 for backlit close-up subjects.

<sup>†</sup> Subjects shaded from sun but lit by large area of clear sky.

#### **Adjustments for Long Exposures**

Use the adjustments in the following table when working with long exposure times.

| Film | Calculated Exposure Time (Sec) Exposure increases include adjustment required for KODAK Color Compensating Filters |                    |                        |                 |
|------|--|--------------------|------------------------|-----------------|
| Code | 1/10,000 to<br>1/100   | 1/10               | 1                      | 10              |
| PKM  | None   |                    | +1/2 stop<br>No filter | Not recommended |
| PKR  | None   | +1/3 stop<br>CC05R | Not recommended        |                 |
| PKL  | None   |                    | +1/2 stop<br>CC10Y     | Not recommended |

**Note:** This information applies only when exposing the films to daylight. The data are based on average emulsions rounded to the nearest ½ stop and assume normal, recommended processing. Using the data only as a guide For critical applications, make test under your conditions.

#### **PROCESSING**

Have these films processed in Process K-14 chemicals. KODACHROME 200 Professional Film can be push-processed to gain film speed or compensate for underexposure. The film can be exposed at EI 500 and pushed 1 ½ stops. It can also be exposed at EI 800 and pushed 2 stops. Be sure to mark your film container with the EI number used and inform the lab that you want the appropriate push processing.

When the film is push processed, the color balance will shift in the magenta-red direction, compensating for some of the greenish artificial illumination present in most stadiums and other large facilities.

We do not recommend push processing of KODACHROME 25 or 64 Professional Films.

#### PRINTING TRANSPARENCIES

You can reproduce images made on KODACHROME Film by using a variety of Kodak products.

#### **Duplicate Color Transparencies**

For direct printing, use—

KODAK PROFESSIONAL EKTACHROME Duplicating Film EDUPE

Or make internegatives on KODAK Commercial Internegative Film, and print them on—

KODAK PROFESSIONAL ENDURA Transparency Optical Display Material

KODAK PROFESSIONAL ENDURA Clear Optical Display Material

#### **Color Prints**

For direct printing, use—

KODAK EKTACHROME RADIANCE III Papers KODAK EKTACHROME RADIANCE III SELECT Material

Or make internegatives on KODAK Commercial Internegative Film, and print them on—

KODAK PROFESSIONAL PORTRA ENDURA Paper KODAK PROFESSIONAL SUPRA ENDURA Paper KODAK PROFESSIONAL ULTRA ENDURA Paper KODAK PROFESSIONAL DURAFLEX® Plus Digital Display Material

KODAK PROFESSIONAL ENDURA Metallic Paper

#### **Digital Files**

You can scan your image to a file and print digitally to—

KODAK PROFESSIONAL ENDURA Transparency Digital Display Material

KODAK PROFESSIONAL ENDURA Clear Digital Display Material

KODAK PROFESSIONAL DURAFLEX® Plus Digital Display Material

KODAK PROFESSIONAL ENDURA Metallic Paper KODAK PROFESSIONAL Day/Night Digital Display Material

### KODACHROME 25, 64, and 200 Professional Film

#### **MORE INFORMATION**

Kodak has many publications to assist you with information on Kodak products, equipment, and materials.

The following publications are available from Kodak customer service, or from dealers who sell Kodak products, or you can contact Kodak in your country for more information.

| E-6    | KODAK Color Films: The Differences Between<br>Professional Films and General Picture-Taking |
|--------|---|
| E-27   | KODAK EKTACHROME 100 Professional Film  |
| E-30   | Storage and Care of KODAK Photographic<br>Materials—Before and After Processing             |
| E-31   | Reciprocity and Special Filter Data for KODAK Films   |
| E-38   | KODAK EKTACHROME Duplicating Films  |
| E-88   | KODACHROME 25, 64, and 200 Films  |
| E-113  | KODAK EKTACHROME 100 Plus Professional Film   |
| E-4024 | KODAK PROFESSIONAL EKTACHROME Films<br>E100G and E100GX                                     |

For the latest version of technical support publications for KODAK PROFESSIONAL Products, visit Kodak on-line at: http://www.kodak.com/go/professional

If you have questions about KODAK PROFESSIONAL Products,

call Kodak.

In the U.S.A.:

1-800-242-2424, Ext. 19, Monday-Friday

9 a.m.-7 p.m. (Eastern time)

In Canada:

1-800-465-6325, Monday–Friday 8 a.m.–5 p.m. (Eastern time)

